Heavy Duty Speed Cushion - 50mm.





Suggested Uses.

- Ideal for heavy traffic areas and where a low impact speed calmer is required.
- Used for areas where trucks are present on a regular basis

Benefits.

<u>Ø28</u> Ø12

- Designed for heavy vehicles disperses the weight load and is also forklift-passable
- Modular interlocking system can be configured to any length
- · Middle sections fitted with high visibility panels
- Rubber construction conforms to uneven surfaces and is coated in EPDM yellow rubber for increased lifespan.

Specifications.

Code	49-SCM
Description	Heavy Duty Speed Cushion - 50mm
Material	Recycled Rubber
Height	50mm
Width	Middle - 500mm / End - 250mm
Length	900mm
Fixings	6 per Mid Section, 3 per end section

Components₋

49-SCMM	Middle Section
49-SCME	End Section
49-FBL	M10 x 100mm Coachscrew and Plug
49-CF10100	M10 x 100mm Anka Bolt



50


50

49-FBL: Asphalt Surface

Drill 14mm dia x 100mm deep hole into asphalt, tap nylon plug into hole. Wind coachscrew into place

49-CF10100: Concrete Surface:

Drill 12mm dia x 125mm deep hole into concrete, clear out dust, insert bolt and tighten.



Scan here to view the webpage.

