

Dock-PRO folding barriers are designed for the prevention of people and equipment falling into recessed dock areas, off platforms and into service pits.

The lift-a-way design has the required top and mid-rail configuration, which is simply lifted and nested out of the way overcoming the need of having to keep swing areas clear. This is an excellent space-saving alternative.

In the situation where ceiling height is limited, Dock-PRO Bifold is the answer. The wide opening can be protected with minimal height required.

▶ BENEFITS

- Ease of operation – gas strut assist
- No pinch points
- Excellent for the low head height application
- Extremely space efficient
- Dimension flexibility to accommodate custom widths
- Powder-coated finish: yellow

▶ SPECIFICATIONS

Code: 49-DFB (single)

Description: Dockpro Folding Barrier, with receiver post

Material: Steel - Galvanised & powder coated

Size: 1m high x up to 3100mm wide overall (including mounting posts)
Height when open: 3820mm. Width of gap when open: 2770mm



Single Dock-PRO

Code: 49-DFB-BF (bifold)

Description: Dockpro Folding Barrier, with receiver post - Bi-fold

Material: Steel - Galvanised & powder coated

Size: 1m high x up to 3100mm wide overall (including mounting posts)
Height when open: 2300mm. Width of gap when open: 2530mm



Bifold Dock-PRO