

# Bollards - Removable, Key Operated



## Surface Mount Removable Bollard

The Surface Mount Removable Bollard is designed for applications where the ground cannot be core drilled or penetrated significantly, such as suspended or prestressed slabs, or underground services.

The bollard locks into the surface mounted receiver shoe via an internal locking system using high security locks and can be removed to allow vehicle access.

- Height: 950mm
- 90mm(Dia)
- Receiver shoe: 18(H) x 200mm(W)
- 2 keys supplied per bollard



CODE	DESCRIPTION	SIZE (mm)
49-SMR90	Surface Mount Removable Bollard	950(H) x 90(D)
49-CF10100	Fastener - Concrete	M10 x 100 Anka Screw

4 fasteners required per bollard.

## Key Operated Folding Bollard

Use to prevent vehicles from entering pedestrian thoroughfares and for parking space protection. Base plate bolts down onto your existing surface and easy-to-use key-lock function enables bollard to be folded down or locked into upright position.

- Height: 650mm
- 60mm(Dia)
- 110mm high when folded down
- 2 keys supplied



CODE	DESCRIPTION	SIZE (mm)
49-KOPB	Key Operated Folding Bollard	650(H) x 60(D)
49-CF10	Fasteners - Concrete	M10 x 75 Anka Screw
49-FB	Fasteners - Bitument	M10 x 75 C/Screw & Plug

4 fasteners required per bollard.